

Pressure Monitor

PM V2.2

Date: 21.02.2020
Version: 1.2

Product summary

Pressure monitor for SingleUse pressure sensors

Features

- 2 x sensor input for PendoTech / SciLog SingleUse sensors
- Single pressure / differential pressure
- Tare and offset correction
- Analog output (0..10 V and 4 ..20 mA)
- Programmable relais output

Applications

- Pressure monitoring
- Bioreactor process control
- Filter condition surveillance



Compatible pressure sensors



Parker SciPress



PendoTech PRESS-S-x

Technical Data

Input Voltage	24 VDC
Controller current consumption	< 50 mA
Compatible sensor types	PendoTech PRESS-S-xx Parker (SciLog) SciPress
Pressure range	0 .. 2 bar
Accuracy	±0.1 % full scale
Digital inputs (tara, tara clear)	Opto-isolated, signal = 5 ... 24 VDC
Analog output (single/differential pressure)	0 .. 10 VDC 4 .. 20 mA
Relais output	1 change-over contact, internal (24 V) or external supply
Interface	3 line text display, user buttons
Mechanical dimensions: (L x W x H)	104 x 69 x 26 mm, anodized alloy housing
Weight	140 g
Protection	IP 40

ReseaTech GmbH | Pestalozzistrasse 16 | 3400 Burgdorf | Switzerland
www.reseatech.ch | info@reseatech.ch

This information corresponds to the current state of knowledge. Reseatech reserves the right to make technical changes. Liability for consequential damage resulting from the use of Reseatech products is excluded